

Battery Technical Specification
6-CD45/TS - 7.2V 4.5Ah
High Temperature Nickel Cadmium



2 x 220mm(l) x ø 37mm
Fixing Centres 205mm each

Technical Details:

| | |
|---------------------|--------------|
| Nominal Voltage (V) | 7.2 Volts |
| Nominal Capacity | 4.5Ah @ 25°C |

Dimensions:

| | |
|------------------------|-----------------------|
| With End Caps | 2 x 220mm x Ø 37.0mm |
| End Cap Fixing Centres | 2 x 205mm |
| Without End Caps | 2 x 177mm x Ø 32.5mm |
| Weight | 792 g (with end caps) |

Temperature:

| | | | |
|-------------------------|----------|-------------|---------------|
| Charge - Standard | 15 Hours | 0 to + 55°C | 450mA (0.10C) |
| Charge - Trickle | 24 Hours | 0 to + 55°C | 200mA (0.05C) |
| Storage (within 1 Year) | | 0 to + 25°C | |

There are 2 versions available -

Order Codes

| | |
|----------------|--|
| 6-CD45/TS/NECA | 7.2V 4.5Ah Without End Caps with Irreversible Socket |
| 6-CD45/TS/AS | 7.2V 4.5Ah With End Caps & Irreversible Socket |



Batteries supplied with leads are fitted with an irreversible socket & 30cm of cable.
ENSURE CORRECT POLARITY

